



• QUALITY

• SERVICE

• INTEGRITY



## Hamilton Drywall Products Ready-Tex

is a pre-mixed, aggregate-free, white and versatile wall and ceiling texture. Ready Tex adheres well to a variety of properly prepared substrates including drywall, plaster, concrete and brick. Apply by spraying or by hand using a variety of tools to achieve fine, medium, coarse and knock-down texture finishes. Ready-Tex mixes, sprays and atomizes easily, has excellent workability and very good coverage and stand-out/definition.

### Job Conditions:

Maintain a minimum air, surface and texture material temperature of 10° C (50° F) for 48 hours prior to application and until "dry" and stable.

### Surface Preparation:

All surfaces must be firm, clean, dry and free of foreign substances.

The absorption rate of the surface that Ready Tex is applied to may cause variation in the texture pattern.

NEW DRYWALL should be primed with one or more coats of Hamilton's Prep-Tex Plus prior to texture application. Paint must be completely dry prior to texture application.

CONCRETE surfaces must be aged at least 60 days prior to texture application. Particular caution should be exercised to determine the presence of efflorescence, dirt, dust, grease, separating and/or bond breaking agents, or a latent layer of cement. After removal of any of the foregoing, any irregularities in the concrete surface should be filled and smoothed with the appropriate Hamilton products.

### Mixing:

In a clean container mix mechanically to a smooth, creamy consistency, adding more water as required.

### Application:

For interior use only.

To avoid cracking do not apply in thickness exceeding 4 mm in a single application. Ready-Tex can be applied with a variety of equipment. For spray applications a hand held hopper, stator tube or pressure pot machine can be used. For hand application a variety of tools can be used including trowels, putty knives, rollers, brushes, sponges or brooms.

### Coverage/Yield:

Heavy spray: Approx. 20-40 square meters (200-450 square feet) per 15.5 liter carton.

Light spray: Approx. 40-60 square meters (450-650 square feet) per 15.5 liter carton.

Hand application: Approx. 5-20 square meters (50-200 square feet) per 15.5 liter carton.

Approximate yield per 15.5 liter carton (adjusted to spray consistency) – 20 liters.

### Storage/Shelf Life:

Rotate inventory within 60 days of the production date on the package. Store in a dry environment away from freezing, extreme heat and direct sunlight.



Submittal Approval  
Stamp / Signature