



• QUALITY

• SERVICE

• INTEGRITY



## Hamilton Drywall Products Light Weight Taping

is a high performance, pre-mixed, drywall joint compound. Specially formulated for embedding drywall tape and paper bead trim, and for skim coating. Light Weight Taping has excellent workability, open-time and slip. Offers a smooth application, does not sag and provides exceptional bond between tape and drywall surface paper.

### Standards:

Light Weight Taping meets or exceeds ASTM C-475 "Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board".

### Job Conditions:

Maintain a minimum air, surface and compound temperature of 10° C (50° F) for 48 hours prior to application and until "dry" and stable.

### Surface Preparation:

All surfaces must be firm, clean, dry and free of foreign substances. Open spaces between panels of 3mm (1/8") or more should be pre-filled with compound at least 24 hours prior to embedding or first coat work. Hamilton Drywall Products Ultra-Fill or Smooth Set Lites are recommended for larger fills.

### Mixing:

In a clean container mix mechanically to a smooth, creamy consistency, adding water as required. Add water in 125 ml (1/2 cup) increments to avoid over thinning.

### Application:

For interior use only. Apply with hand or mechanical tools. Fill joint with a thin layer of compound, embed tape - leaving about 0.8 -1 mm (1/32") of compound under the tape - wipe lightly to remove excess compound and let dry. Allow compound to dry thoroughly before filling and finishing.

### Coverage/Yield:

15.5 liter carton - Approximate coverage - 130-150 square meters (1400-1614 square feet). Approximate yield - 15.5-20 liters depending on application type.

18 liter pail - Approximate coverage - 150-174 square meters (1614-1872 square feet). Approximate yield - 18-26 liters depending on application type.

### Storage/Shelf Life:

Rotate inventory within 60 days of the production date on the package. Store in a dry environment, away from freezing, extreme heat and direct sunlight. For best results use within 6 months.



Submittal Approval  
Stamp / Signature