



• QUALITY

• SERVICE

• INTEGRITY



Hamilton Drywall Products Prep-Tex Plus

is a premium quality, fast drying, high coverage texture undercoat specifically formulated for use over new interior gypsum wallboard prior to texture application. A vinyl acrylic product with excellent wet and dry hide, very low sheen, high solids and excellent sag resistance; Prep-Tex Plus reduces surface variations prior to texture application for a more even finish.

Job Conditions:

Maintain a minimum air, surface and texture material temperature of 10° C (50° F) for 48 hours prior to application and until "dry" and stable.

Surface Preparation:

Substrate must be dry, clean, sound and free from dust.

For best results, drywall joints, fasteners, and trims should be concealed using Hamilton Drywall Products Joint Compounds in accordance with GA-214/ASTM C-840 to a minimum Level 4 finish.

Mixing:

Mix well before using.

Application:

For interior use only.

Apply a full coverage coat with an air or airless sprayer to 5 mils wet film thickness minimum, with a .019" to .021" spray tip.

Drying Time:

Dry to touch in 20-40 minutes at 20°C (68°F) and good ventilation. Paint must be completely dry prior to texturing.

Clean Up:

Clean tools and equipment with warm soapy water, rinse with clean water.

Coverage/Yield:

Approximately 110-170 square meters (1200-1800 square feet) per 18.9 liter pail.

Decoration:

Prep-Tex Plus is designed to be applied to properly finished new drywall surfaces prior to texture application. Not recommended for re-painting old textured surfaces. This product is not intended for use as a final decorative surface. Must be completely dry prior to subsequent decoration.

Storage/Shelf Life:

Rotate inventory regularly. Store in an environment away from freezing, extreme heat and direct sunlight.



Submittal Approval
Stamp / Signature