



• QUALITY

• SERVICE

• INTEGRITY



Hamilton Drywall Products Light Weight All Purpose

is a pre-mixed, high performance, drywall joint compound. Used for embedding drywall tape and paper bead trim, and for filling and finishing drywall joints, fasteners and trims. Light Weight All Purpose has excellent workability and working-time, low shrinkage, good slip and sandability, goes on smooth providing a smooth and durable finish.

Standards:

Light Weight All Purpose meets or exceeds ASTM C-475 "Standard specification for Joint Compound and Joint Tape for Finishing Gypsum Board".

Job Conditions:

Maintain a minimum air, surface and compound temperature of 10° C (50° F) for 48 hours prior to application and until "dry" and stable.

Surface Preparation:

All surfaces must be firm, clean, dry and free of foreign substances. Open spaces between panels or voids of 3mm (1/8") or more should be pre-filled with compound at least 24 hours prior to tape embedding or first coat work. Hamilton Drywall Products Ultra-Fill or Smooth Set Lites are recommended for larger fills.

Mixing:

In a clean container mix mechanically to a smooth, creamy consistency, adding more water as required. Add water in 125 ml (1/2 cup) increments to avoid over thinning.

Application:

For interior use only. Apply with hand or mechanical tools. Allow compound to dry thoroughly between coats. When sanding, use 180-grit or finer sandpaper or 220-grit mesh cloth. Avoid scuffing gypsum panel paper.

Coverage/Yield:

15.5 liter carton - Approximate coverage - 45 - 70 square meters (484-754 square feet). Approximate yield - 15.5-20 liters depending on application type.
18 liter pail - Approximate coverage - 52 - 81 square meters (562 - 876 square feet). Approximate yield - 18-26 liters depending on application type.

Storage/Shelf Life:

Rotate inventory within 60 days of the production date on the package. Store in a dry environment away from freezing, extreme heat and direct sunlight. For best results use within 6 months.



Submittal Approval
Stamp / Signature